

## Product Information

Transparent Polyester film coated with a cross-linked acrylic adhesive offering excellent temperature resistance, ageing and UV stability.

The adhesive can be removed without residue even after long periods of usage.

POLI-TACK 853 transfer film is suitable for thermal transfer of heat sealing substrates, i.e. for the transfer of Flock- and Flex-film onto textiles.

## Technical Data

Carrier:	PET-film, transparent	
Adhesive:	Acrylic	
Adhesion [N/cm]:	0,30	+/- 10 %
Thickness [mm]:	0,12	+/- 5 %
Liner:	Siliconised PP film, white	

## Standard Dimensions

500 mm x 10 m  
500 mm x 25 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.